

# DIRTCUB HYDRAULIC DUMP-BOX LIGHT FOOTPRINT TRAILER



The DirtCub from TYCROP is the first dump-box designed specifically to be towed behind turf utility vehicles.

It's 4-Wheel Walking-Beam Suspension gives it the lightest footprint in the industry - allowing travel over sensitive areas even when fully loaded.

The multiple uses of the DirtCub make it a valuable addition to your golf course maintenance program.



# A CLOSER LOOK



## STAKE POCKETS

These sidewall pockets allow for your own removable side extensions to increase box volume for maximum capacity of lighter-weight materials.

## BIG BED, BIG LOAD

The all-steel construction DIRT CUB carries 3000 pounds (1360 kg) in its 5'x6' (1.5m x 1.7m) bed and remains stable and maneuverable even under heavy payloads. Plus, it keeps your utility bed free for other tools and equipment.



## OPTIONAL TOOL CADDY

Keeps rakes and shovels at the ready and out of the trailer bed.

## HINGED TAILGATE

The DIRT CUB's reinforced tailgate provides a solid extension for longer loads and for placing pallets with a forklift.

## HYDRAULIC CYLINDER

Variable control of the cylinder allows for gradual raising of the bed for fast or slow distribution of material. The trailer bed raises to provide over 50 degrees of dump angle.

## ADJUSTABLE HITCH

The fully adjustable hitch height allows the unit to be towed by a variety of heavy-duty utility vehicles.



## WALKING BEAM SUSPENSION

Four-wheel walking beam suspension provides low ground pressure and stability. All four tires maintain contact with the turf regardless of the terrain and the payload weight remains evenly distributed on a 64" (1.6m) wheelbase - minimizing any footprint.

## BALANCED DESIGN

Uniquely engineered to maintain a stable tongue weight - even when the bed is fully elevated.



## TOW VEHICLE REQUIREMENTS:

Towing Capacity (max. payload): 3,400 lb (1,550 kg)  
Tongue Weight (max. payload): 300 lb (136 kg)  
Minimum Power: 18hp (13Kw)

## SPECIFICATIONS:

Bed Size: 60 13/16" W x 70 1/8" L (1.54m x 1.78m)  
Unit Size: 68 1/8" W x 45 9/16" H  
Weight: 956 lbs. (437 kg)  
Payload: 3000 lbs. (1360 kg)  
Suspension: 4 wheel walking beam  
Tire Size: 24x13x12 in (60x32.5x30 cm), 4 ply  
Inflation: 18 psi (124 kPa)

